



17.600 W.



400° C



250 Kg.



400 / 50/60 Hz


CARACTERÍSTICAS features

- | | |
|---|---|
| <ul style="list-style-type: none"> ● DIMENSIONES INTERNAS: 2 x (W)1054 x(D)700x(H)169 mm
<i>cooking chamber dimension</i> | <ul style="list-style-type: none"> ● POTENCIA: 17.600 W
<i>power</i> |
| <ul style="list-style-type: none"> ● DIMENSIONES EXTERNAS: (W)1355x(D)945x(H)660 mm
<i>external dimension</i> | <ul style="list-style-type: none"> ● TEMPERATURA MÁXIMA: 400° C
<i>max temperature</i> |
| <ul style="list-style-type: none"> ● CONEXIÓN: Trifásica 3F+N+T
<i>3p + n + e three phase</i> | <ul style="list-style-type: none"> ● PESO: 250 Kg.
<i>weight</i> |
| <ul style="list-style-type: none"> ● Superficie de cocción de material refractario de alta calidad
<i>cooking surface high-quality refractory material</i> | <ul style="list-style-type: none"> ● VOLTAJE: 400 / 50/60 Hz
<i>Voltage</i> |

EQUIPAMIENTO equipment

- Regulación temperatura suelo / techo independiente *independent base / top temperature control*
- Lámpara interior *Halogen chamber light*
- Termómetro *Thermometer*

PVP rrp HP-1233