

# STC 1011 E



## DECLARACIÓN DE CONFORMIDAD DECLARATION OF CONFORMITY

Directiva(s) del Consejo con la(s) que se declara conformidad:  
*Council Directive(s) to which conformity is declared:*

**DC 2014/35/EU + DC 2014/30/EU + DC 2011/65/EU**

Aplicación de las Normas:  
*Application of the Standards:*

**EN 60335-1:2012 / EN 60335-2-42:2003 + Corr:2007 + A1:2008 + A11:2012 /  
EN 55014-1:2006 + A1:2009 + A2:2011 / EN 55014-2:1997 + A1:2001 + A2:2008 / EN 61000-3-2 :2006  
+ A1:2009 + A2:2009 / EN 61000-3-3 :2008**

Fabricante / *Manufacturer's*  
*name:*

**FM CALEFACCIÓN S.L.  
CIF: B-14343594**

Dirección / *Manufacturer's*  
*address:*

**CTRA. de Rute km.2.700, C.P.:14900, Lucena  
Cordoba, España**

Tipo de equipo / *Type of*  
*equipment:*

**HORNO / OVEN**

Marca / *Trade.:*

**FM CALEFACCIÓN**

Modelo / *Model no.:*

**STC 1011 E**

**Nosotros, los abajo firmantes, declaramos bajo nuestra exclusiva responsabilidad que el equipo especificado cumple con la(s) Directiva(s) y Norma(s) mencionadas**

***We, the undersigned, hereby declare under our sole responsibility that the specified equipment is in conformity with the above Directive(s) and Standard(s)***

Lugar / *Place:* **Lucena**

Firma / *Signature:* **B-14785315**

Fecha / *Date:* **01/10/2019**



# STC 1011 E



| TECHNICAL CHARACTERISTICS |                               | CONNECTIONS |                            |
|---------------------------|-------------------------------|-------------|----------------------------|
| Empty unit weight         |                               | 1           | Hose connection            |
| Unit+packaging weight     |                               | 2           | Hood                       |
| Supply voltage            | 400 Vac - three phase         | 3           | Fumes condenser connection |
| Frecuency                 | 50/60 Hz                      | 4           | Water connection           |
| Power cable               | Hose 3F+N+T 4 mm <sup>2</sup> | 5           | Drain Ø40 mm               |
| Sound pressure level      | Lower than 70 dB              | 6           | On/Off button              |
| Total power               | 11400 W                       | 7           | Safety gap ≥120 mm         |
| Thermal power             | 11000 W                       | 8           | Fumes exit Ø 50 mm         |
|                           |                               | 9           | Safety thermostat reset    |

\*Dimensions in mm

